


# Ceramic Tactile Indicators



300 x 300mm  
Top of Dome: 25mm  
Bottom of Dome: 35mm  
Height of Dome: 5mm  
Thickness: 10mm



Colours Available:  
Ivory  
Black  
Yellow  
Grey

**The Ceramic Range** is made from Fine Porcelain and is the most economical Tactile Indicator product currently available in the market. It comes in four colours to meet the standard requirement of Luminance contrast as required by AS/NZS 1428.4.

Tactile Indicators provide both directional and hazard warnings which can be used internally and externally in situations such as stairways, ramps, escalators, kerbs, car park crossings, railway platforms, passenger wharves, bus stops and overhead hazards.

## Ceramic Tactile Indicators

**Benefits and Technical Details:** Ceramic Tactile Indicators meet or exceed the performance criteria specified in the following tests or standards:

1. **Testings (Performed by CSIRO)**

AS/BZS 4586 Appendix A *Wet Pendulum 4S W*.  
AS/NZS 4586 Appendix D *Oil Wet Ramp Test R12*  
Dry 44.09 / Wet 42.30  
Mean Contrast Range 29.6 – 57.3  
AS 4459.4 *Breaking Load 2242N, Breaking Strength 2092 N, Modules of Rupture 31.39 N/mm<sup>2</sup>*  
ISO 10545-3 *Water Absorption 0.19%*

2. **Slip Resistance**

Rating WR12 AS/NZS 4586:2004

2. **Australian Standards**

Manufactured according to AS/NZS1428.4 2002 (F)

3. **Luminance**

AS/NZS 1428.4 *Wet & Dry Luminance Reflectance*

4. **Easy Cleaning**

*Washability:*

Regular cleaning to remove built up dirt and objects on the Tactile Indicators will ensure continued performance. Vacuuming or brushing with a stiff bristle head (dry or wet) is often enough to keep Tactile Indicators clean. Do not use highly alkaline or acidic cleaning agents. The pH of the cleaning agents should be between pH5 and pH12.