


RolaDek® Entrance Mats With High Traffic Tread



JUS-2009
GECA 25-2005-
Floor Covering Products

An environmentally preferable product certified by Good Environmental Choice Services Pty Ltd to the requirements of the Environmental Choice Australia mark



RolaDek® Entrance Mats feature a sleek architectural appearance with perforated aluminium hinge construction. Perfect for use in all high traffic environments, RolaDek® Entrance Mats stand up to the debris and dirt without sacrificing aesthetics.

All RolaDek® Entrance Mats feature:-

- Easy to clean – roll back 180°.
- Custom fabrication, including angles, arcs/radii and cutouts.
- Continuous resilient vinyl cushion for superior noise reduction.
- Male and female EPDM Rubber edging for on-site trimming.
- Rolling load test to 160 kg./wheel
- Metal Coating Colours Available – Clear, Bronze, Black
- High Traffic Tread available in Charcoal.



Benefits and Technical Details: RolaDek® Entrance Mats with High Traffic Treads meet or exceed the performance criteria specified in the following tests or standards:

1. Aluminium

Aluminium RolaDek® Rail punched and anodised in clear 15um 6063-T5 Aluminium alloy.

2. Vinyl

British Standard Softness – BS2782 – Value: 20±5

Shore A Hardness (10sec) ASTM D2240 - 90±

Specific Gravity – BS 2782 – 1.36

Tensile Strength – BS 2782 – MPA

Elongation at Break – BS2782

Complies with the current RoHS requirements relating to hazardous substances.

3. High Traffic Insert

Composition: Adipic Acid – hexamethylenediamine 032131-17-2 TLV:10ppm >99

Ethoxylated Components Proprietary TLV: 10ppm <0.02

Flash Point: 581-592 degrees F Method: ASTM-D 1929-77

Autoignition temperature: 905 degrees F Method: ASTM-D 1929-77